

Product: STREETPARK MINI LED PREMIUM HE 8000 FLOOD E IP66 21 740

Index: 19.3176.0014.21



Description

Powder painted aluminum cast housing highly weather proof. Luminaire is equipped with adjustable handle designed for mounting on posts and arms of 48 mm diameter. Level of tightness IP66. Diffuser is made of hardened glass. Following color temperatures are available: 4000 K. It is possible to program an autonomous multi-level or manual power reduction for specific customer needs by using a specialized power supply in the luminaire.

Product information

Category	Outdoor luminaires
Family	STREETPARK MINI LED PREMIUM
Name	STREETPARK MINI LED PREMIUM HE 8000 FLOOD E IP66 21 740
Index	19.3176.0014.21
EAN	5902107272913














Light and electrical data

Light source	LED
Luminous flux LED [lm]	8090
LED power [W]	49
Luminaire luminous flux [lm]	7538
Power of luminaire [W]	55
Luminaire's light efficiency [lm/W]	137,1
Color of the light [K]	4000
CRI	>70
Beam angle [°]	(C0-C180) / (C90-C270) - 119° / 117,6°
Protection against electric shock	I
Protection degree	IP66
Voltage	220240 V, 5060 Hz
Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 100000
	·
Lifetime of LED sources [h]	100000
Lifetime of LED sources [h] Lx/By	100000 L80/B10
Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	100000 L80/B10 -40 ÷ 40


Mechanical data



Assembly	mounted on poles
Material	aluminum
Color	RAL 9006 (grey)
Diffuser	hardened transparent glass
Impact resistant	IK09
Weight [kg]	3,11
Dimensions [mm]	507 x 209 x 144



A graph of light



Accessories

Index 50EL60/48X100

Name Redukcja słupa 60/48x100 do oprawy



Index 19.3100.0001.21

Name Pole Mounting Bracket for STREETPARK Fi 50



Index 19.3100.0002.21

Name Pole Mounting Bracket for STREETPARK Fi 60

