

**Product:** STREETPARK SMALL LED PREMIUM HO 15000 STREET-S E IP66 21 740

**Index:** 19.3177.0015.21



## Description

Powder painted aluminum cast housing highly weather proof. Luminaire is equipped with adjustable handle designed for mounting on posts and arms of 60 mm diameter. Level of tightness IP66. Diffuser is made of hardened glass. Following color temperatures are available: 4000 K. It is possible to program an autonomous multi-level or manual power reduction for specific customer needs by using a specialized power supply in the luminaire.

## Product information

Category	<b>Outdoor luminaires</b>
Family	<b>STREETPARK SMALL LED PREMIUM</b>
Name	<b>STREETPARK SMALL LED PREMIUM HO 15000 STREET-S E IP66 21 740</b>
Index	<b>19.3177.0015.21</b>



## Light and electrical data


Light source	<b>LED</b>
Luminous flux LED [lm]	<b>15350</b>
LED power [W]	<b>99</b>
Luminaire luminous flux [lm]	<b>13005</b>
Power of luminaire [W]	<b>111</b>
Luminaire's light efficiency [lm/W]	<b>117,2</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;70</b>
SDCM (LED sources)	<b>5</b>
Beam angle [°]	<b>street light distribution</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP66</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>100000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>-40 ÷ 40</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>6 (B10), 10 (B16), 10 (C10), 17 (C16)</b>

## Mechanical data

Assembly	<b>mounted on poles</b>
Material	<b>aluminum</b>
Color	<b>RAL 9006 (grey)</b>
Diffuser	<b>hardened transparent glass</b>
Impact resistant	<b>IK09</b>
Dimensions [mm]	<b>620 x 260 x 188</b>



## A graph of light



## Accessories

Index 19.3100.0001.21

Name Pole Mounting Bracket for STREETPARK Fi 50



Index 19.3100.0002.21

Name Pole Mounting Bracket for STREETPARK Fi 60

