


Product: X-LINE SURFACE 1x E27 PLX 24 / POD ŹRÓDŁO PARATHOM STICK

Index: 19.3101.0002.24



Description

Luminaire for replaceable sources with a popular E27 base made of aluminum profile equipped with a opal diffuser. Installation depending on the version is ceiling mounted (X-Line Surface) or on the wall (X-Line Kinkiet). The luminaire must be equipped with a Parathome Stick source for the E27 base.

Product information

| | |
|----------|--|
| Category | Surface mounted luminaires |
| Family | X-LINE E27 |
| Name | X-LINE SURFACE 1x E27 PLX 24 / POD ŹRÓDŁO PARATHOM STICK |
| Index | 19.3101.0002.24 |
| EAN | 5902107254117 |



Light and electrical data

| | |
|-------------------------------------|--|
| Light source | LED E27 PARATHOM STICK (not included) |
| Luminous flux LED [lm] | depending on source |
| LED power [W] | depending on source |
| Luminaire luminous flux [lm] | depending on source |
| Power of luminaire [W] | depending on source |
| Luminaire's light efficiency [lm/W] | depending on source |
| Color of the light [K] | depending on source |
| CRI | depending on source |
| SDCM (LED sources) | depending on source |
| Beam angle [°] | (C0-C180) / (C90-C270) - 113,2° / 114,4° |
| Protection against electric shock | I |
| Protection degree | IP44 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | depending on source |
| Lx/By | depending on source |
| Driver | none |

Mechanical data



| | |
|------------------|----------------------------|
| Assembly | surface mounted on ceiling |
| Material | aluminum |
| Color | anodised aluminum |
| Diffuser | PLX (PMMA opal) |
| Impact resistant | IK04 |
| Weight [kg] | 0,8 |
| Dimensions [mm] | 250 x 63 x 74 |

A graph of light

