

Product: UPDOOR MINI LED 2000 PC 840 E IP65 04

Index: 19.3137.0001.04



Description

Powder painted steel housing. Possibility of mounting emergency module. Isolated battery applied in luminaire is equipped with thermostat enabling performance in low temperature up to -25°C . Updoor Mini might be mounted on walls or ceilings and is recommended to illuminate buildings' entrances, arteries, tunnels, underground entrances, etc.

Product information



Category	Outdoor luminaires
Family	UPDOOR MINI LED
Name	UPDOOR MINI LED 2000 PC 840 E IP65 04
Index	19.3137.0001.04



Light and electrical data

Light source	LED
Luminous flux LED [lm]	2055
LED power [W]	12
Luminaire luminous flux [lm]	1295
Power of luminaire [W]	14
Luminaire's light efficiency [lm/W]	92,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	2
Beam angle [°]	(C0-C180) / (C90-C270) - 100,6° / 103,2°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	>100000
Lx/By	L80/B10
Operating temperature range [°C]	5÷30 / -25÷30 THERMOSTAT
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	61 (B10), 98 (B16), 102 (C10), 164 (C16)

Mechanical data



Assembly	mounted on wall
Material	steel sheet
Color	RAL 9005 (black)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK08
Weight [kg]	1,4
Dimensions [mm]	190 x 150 x 150

A graph of light

