

Product: ATENA LINE NEW OUTDOOR LED 36000 SH ASY E IP65 04 840 Index: 19.3138.0035.04



А


Description

Outdoor luminaire dedicated for pole mounting, ceiling mounting or for hanging mounting. The external application is possible due to the fact that the product is equipped with a pressure compensation valve, and the housing has a special painting adapted to the external conditions. Rectangular housing made of aluminum sheet. Only one colour available: RAL 9005 (black). Upon client request there is a possibility to make longer luminaire than standard dimensions. Consequently, the luminaire will have bigger luminous flux. The light sources are protected by diffuser made of hartened glass and the whole construction is characterized by high level of protection against dust amd water penetration-IP65.

Product information		Category Outdoor luminaires		
		Family	ATENA LINE NEW	
		Name ATENA LINE NEW OUTDOOR LED 36000 SH ASY E IP65 04 840		
		Index	19.3138.0035.04	
		EAN	5902107281366	
Light and electrical data		Light sour	се	LED
		Luminous	flux LED [lm]	37271
		LED powe	r [W]	208
		Luminaire	luminous flux [lm]	27446
		Power of l	uminaire [W]	210
		Luminaire'	s light efficiency [lm.	/W] 130,7
		Color of th	e light [K]	4000
		CRI		>80
		SDCM (LE	D sources)	3
		Beam ang	le [°]	asymmetric light distribution - Imax=-54°
		Protection	against electric sho	ck I
		Protection	degree	IP65
		Voltage		220240 V, 5060 Hz
		Lifetime of	LED sources [h]	83000
		Lx/By		L90/B10
		Operating	temperature range	[°C] -25 ÷ 40
		Driver		standard on/off (E)
		Power fact	tor cos φ	>0,95
		Circuit loa	d capacity	7 (B10), 11 (B16), 7 (C10), 11 (C16)
Mechanical data		Assembly		mounted on poles; directly mounted to ceiling construction or surface mounted on slings
		Material		aluminum
	т	Color		RAL 9005 (black)

Material	aluminum
Color	RAL 9005 (black)
Diffuser	SH (transparent hardened glass)
Impact resistant	IK08
Dimensions [mm]	680 x 201 x 150

A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025