

**Product:** STREETPARK MINI LED COMPACT HO 5500 STREET-M E IP66 21 740

**Index:** 19.3251.0036.21



## Description

Powder painted aluminum cast housing highly weather proof. Luminaire is equipped with adjustable handle designed for mounting on posts and arms of 48 mm diameter. Level of tightness IP66. Diffuser is made of hardened glass. Following color temperatures are available: 4000 K. It is possible to program an autonomous multi-level or manual power reduction for specific customer needs by using a specialized power supply in the luminaire. The luminaires have overvoltage protection as standard based on the functionality of the power supplies.

## Product information

Category	<b>Compact</b>
Family	<b>STREETPARK MINI LED COMPACT</b>
Name	<b>STREETPARK MINI LED COMPACT HO 5500 STREET-M E IP66 21 740</b>
Index	<b>19.3251.0036.21</b>
EAN	<b>5902107272876</b>



## Light and electrical data


Light source	<b>LED</b>
Luminous flux LED [lm]	<b>5755</b>
LED power [W]	<b>37</b>
Luminaire luminous flux [lm]	<b>4751</b>
Power of luminaire [W]	<b>42</b>
Luminaire's light efficiency [lm/W]	<b>113,1</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;70</b>
Beam angle [°]	<b>street light distribution</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP66</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>100000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>-40 ÷ 40</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>22 (B10), 35 (B16), 37 (C10), 59 (C16)</b>

**Mechanical data**




Assembly	mounted on poles
Material	aluminum
Color	RAL 9006 (grey)
Diffuser	hardened transparent glass
Impact resistant	IK09
Dimensions [mm]	507 x 209 x 144

**A graph of light**



**Accessories**

Index 50EL60/48X100  
Name Redukcja słupa 60/48x100 do oprawy



Index 19.3100.0001.21  
Name Pole Mounting Bracket for STREETPARK Fi 50



Index 19.3100.0002.21  
Name Pole Mounting Bracket for STREETPARK Fi 60

