

Product: BACKPANEL LED 3800 MICRO-PRM E 34 IP20/44 830 1200X300

Index: 19.3213.0029.34



Description

Modern LED panel dedicated to be mounted on suspended modular ceilings, cardboard suspended ceilings (using adaptive frame), directly on the ceiling (using adaptive frame) or using adaptive frame and suspensions. Equipped with the highly efficient LED sources. Direct light distribution. Luminary body made from steel sheet. PMMA opal diffuser. Colour of luminary - white. CRI>80. Luminary dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc.

Product information

Category	Recessed luminaires
Family	BACKPANEL LED
Name	BACKPANEL LED 3800 MICRO-PRM E 34 IP20/44 830 1200X300
Index	19.3213.0029.34
















Light and electrical data

Light source	LED	
Luminous flux LED [lm]	3728	
LED power [W]	18,4	
Luminaire luminous flux [lm]	3281	
Power of luminaire [W]	20,6	
Luminaire's light efficiency [lm/W]	159,2	
Color of the light [K]	3000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 88,6° / 93°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	II	
Protection degree	IP20/44	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 30	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	
Circuit load capacity	31 (B10), 50 (B16), 50 (C10), 80 (C16)	



Mechanical data	Assembly	mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories
В	Material	steel sheet
L TH	Color	RAL 9016 (white)
A	Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
	Impact resistant	IK04
	Weight [kg]	3,1
	Dimensions [mm]	1195 x 295 x 34

A graph of light



Accessories

Index 19.3213.0080.34

Name BACKPANEL LED RECESSED ACCESSORIES 34 / 1200X300



Index 19.3213.0074.34

Name BACKPANEL LED SURFACE ACCESSORIES 34 / 1200X300



Index 19.3213.0077.34

Name BACKPANEL LED ACCESSORIES SET WITH SUSPENSION 1,5M / 1200X300

