

Product: AGAT CLEAN-ECO LED COMPACT 8000 SHM E IP65 840 / 1200X300

Index: 19.3236.0005.34



Description

Luminaire designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminaire recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

| | |
|----------|--|
| Category | Compact |
| Family | AGAT CLEAN-ECO LED COMPACT |
| Name | AGAT CLEAN-ECO LED COMPACT 8000 SHM E IP65 840 / 1200X300 |
| Index | 19.3236.0005.34 |



Light and electrical data

| | |
|---|---|
| Light source | LED |
| Luminous flux LED [lm] | 8236 |
| LED power [W] | 49 |
| Luminaire luminous flux [lm] | 6862 |
| Power of luminaire [W] | 55 |
| Luminaire's light efficiency [lm/W] | 124,8 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 98,8° / 102° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP65 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 60000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 12 (B10), 20 (B16), 21 (C10), 34 (C16) |

Mechanical data



| | |
|------------------|-----------------------------------|
| Assembly | mounted in module ceilings |
| Material | steel sheet |
| Color | white |
| Diffuser | SHM (hardened mat glass) |
| Impact resistant | IK08 |
| Dimensions [mm] | 1195 x 295 x 75 |

A graph of light

