

Product: AGAT CLEAN-ECO LED COMPACT 8000 MICRO-PRM E IP65 34 840 / 600X600

Index: 19.3236.0002.34



Description

Luminary designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

Category	Compact
Family	AGAT CLEAN-ECO LED COMPACT
Name	AGAT CLEAN-ECO LED COMPACT 8000 MICRO-PRM E IP65 34 840 / 600X600
Index	19.3236.0002.34














Light and electrical data

Light source	LED
Luminous flux LED [lm]	8236
LED power [W]	49
Luminaire luminous flux [lm]	6347
Power of luminaire [W]	55
Luminaire's light efficiency [lm/W]	115,4
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	12 (B10), 20 (B16), 21 (C10), 34 (C16)




	20100	
1/10/1-1	121111-21	
IVICCI	nanical	uala



Assembly	mounted in module ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	4,4
Dimensions [mm]	595 x 595 x 75

A graph of light





Accessories

Index 2C1A7392-34R

Name EUROPANEL / BACKPANEL / RIM COMPACT LED RECESSED ACCESSORIES 34 / 600X600

