

Product: AGAT CLEAN LED P SMOOTH 3750 MICRO-PRM E IP65 34 830 / 600X300**Index:** 19.4044.1211.34

Description

Luminary designed to module and gypsum and cardboard suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame. The product ensures a homogeneous distribution of light on the iris without shadows and lighter points directly below the LED sources. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

| | |
|----------|----------------------------------------------------------------|
| Category | Clean luminaires - recessed |
| Family | AGAT CLEAN LED SMOOTH |
| Name | AGAT CLEAN LED P SMOOTH 3750 MICRO-PRM E IP65 34 830 / 600X300 |
| Index | 19.4044.1211.34 |
| EAN | 5901867471567 |



Light and electrical data


| | |
|-------------------------------------------|-----------------------------------------|
| Light source | LED |
| Luminous flux LED [lm] | 3668,6 |
| LED power [W] | 17,8 |
| Luminaire luminous flux [lm] | 2865 |
| Power of luminaire [W] | 19,9 |
| Luminaire's light efficiency [lm/W] | 144 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 89° / 89° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP65 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 50 (B10), 90 (B16), 65 (C10), 105 (C16) |

Mechanical data



| | |
|--------------------|--------------------------------------------------------------|
| Assembly | mounted in module ceilings, as well as plasterboard ceilings |
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | Micro-PRM (micro-prismatic diffuser PMMA) |
| Impact resistant | IK04 |
| Weight [kg] | 3,5 |
| Dimensions [mm] | 596 x 296 x 76 |
| Mounting hole [mm] | 580 x 280 |

A graph of light



Accessories

| | |
|-------|---------------------------------------------|
| Index | 2M-X414LKPIPT5 |
| Name | Mounting clips set for plasterboard ceiling |

