

Product: AGAT CLEAN LED P SMOOTH 5400 PLX EDD IP65 34 840 / 600X600

Index: 19.4044.2523.34



Description

Luminary designed to module and gypsum and cardboard suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame. The product ensures a homogeneous distribution of light on the iris without shadows and lighter points directly below the LED sources. Luminary recommended for: emergency departments, intensive care units, and treatment rooms. *Selected luminary variants are available with ENEC certificate.

Product information

Category	Clean luminaires - recessed
Family	AGAT CLEAN LED SMOOTH
Name	AGAT CLEAN LED P SMOOTH 5400 PLX EDD IP65 34 840 / 600X600
Index	19.4044.2523.34
EAN	5902107262549
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	5383,1
LED power [W]	24,8
Luminaire luminous flux [lm]	4010
Power of luminaire [W]	27,8
Luminaire's light efficiency [lm/W]	144,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 105° / 104,8°
Dhatabialagical rick along (IEC/EN	
Photobiological risk class (IEC/EN 62471)	RG0
3 (I I
62471)	
62471) Protection against electric shock	1
62471) Protection against electric shock Protection degree	I IP65
62471) Protection against electric shock Protection degree Voltage	I IP65 220240 V, 5060 Hz
62471) Protection against electric shock Protection degree Voltage Lifetime of LED sources [h]	I IP65 220240 V, 5060 Hz 100000
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By	I IP65 220240 V, 5060 Hz 100000 L80/B10
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	I IP65 220240 V, 5060 Hz 100000 L80/B10 5 ÷ 30




hanical	



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	5,48
Dimensions [mm]	596 x 596 x 76
Mounting hole [mm]	580 x 580

A graph of light



Accessories

Index 2M-X414LKPIPT5

Name Mounting clips set for plasterboard

