

**Product:** RUBIN CLEAN LED P SMOOTH 5400 MICRO-PRM SH EDD IP65 34 840 / 1210X310MM

**Index:** 19.4046.4323.34



## Description

Surface mounted luminary equipped in highly efficient LED sources. Luminary body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame. The product ensures a homogeneous distribution of light on the iris without shadows and lighter points directly below the LED sources. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

## Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED SMOOTH
Name	RUBIN CLEAN LED P SMOOTH 5400 MICRO-PRM SH EDD IP65 34 840 / 1210X310MM
Index	19.4046.4323.34
EAN	5902107308278



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	5948
LED power [W]	26,4
Luminaire luminous flux [lm]	4360
Power of luminaire [W]	29,6
Luminaire's light efficiency [lm/W]	147,3
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	20 (B10), 31 (B16), 33 (C10), 53 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Dimensions [mm]	1210 x 310 x 78

A graph of light

