

Product: RUBIN CLEAN LED P SMOOTH 5400 MICRO-PRM EDD IP65 34 830 / 620X620MM

Index: 19.4046.1513.34



Description

Surface mounted luminary equipped in highly efficient LED sources. Luminary body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame. The product ensures a homogeneous distribution of light on the iris without shadows and lighter points directly below the LED sources. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED SMOOTH
Name	RUBIN CLEAN LED P SMOOTH 5400 MICRO-PRM EDD IP65 34 830 / 620X620MM
Index	19.4046.1513.34
EAN	5902107488840



Light and electrical data

Light source	LED
Luminous flux LED [lm]	5652
LED power [W]	26,4
Luminaire luminous flux [lm]	4414
Power of luminaire [W]	29,6
Luminaire's light efficiency [lm/W]	149,1
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	20 (B10), 31 (B16), 33 (C10), 53 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	620 x 620 x 78

A graph of light

