

Product: RUBIN CLEAN LED P SMOOTH 7500 MICRO-PRM E IP65 34 830 / 620X620MM

Index: 19.4046.1611.34



Description

Surface mounted luminary equipped in highly efficient LED sources. Luminary body made from steel sheet, powder coated in white. Optical systems and diffusors mounted in an aluminum frame. The product ensures a homogeneous distribution of light on the iris without shadows and lighter points directly below the LED sources. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

Product information


Category	Clean luminaires - surface
Family	RUBIN CLEAN LED SMOOTH
Name	RUBIN CLEAN LED P SMOOTH 7500 MICRO-PRM E IP65 34 830 / 620X620MM
Index	19.4046.1611.34
EAN	5901867471710



Light and electrical data

Light source	LED
Luminous flux LED [lm]	7756
LED power [W]	36,4
Luminaire luminous flux [lm]	6057
Power of luminaire [W]	40,8
Luminaire's light efficiency [lm/W]	148,5
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	8 (B10), 13 (B16), 12 (C10), 20 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	5,6
Dimensions [mm]	620 x 620 x 78

A graph of light

