

Product: RUBIN CLEAN LED S SMOOTH 10800 PLX EDD IP65 34 840 / 1160X620MM

Index: 19.4047.2723.34



Description

Surface mounted luminaire equipped in highly efficient LED sources. Luminaire body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame. The product ensures a homogeneous distribution of light on the iris without shadows and lighter points directly below the LED sources. Luminaire recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED SMOOTH
Name	RUBIN CLEAN LED S SMOOTH 10800 PLX EDD IP65 34 840 / 1160X620MM
Index	19.4047.2723.34
EAN	5902107489182



Light and electrical data

Light source	LED
Luminous flux LED [lm]	10766,1
LED power [W]	49,6
Luminaire luminous flux [lm]	8021
Power of luminaire [W]	55,6
Luminaire's light efficiency [lm/W]	144,3
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 105° / 104,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	1160 x 620 x 78

A graph of light

