

**Product:** RUBIN CLEAN LED S SMOOTH 7500 SHM EDD 34 830 / 1210X310MM

**Index:** 19.4047.3413.34



## Description

Surface mounted luminaire equipped in highly efficient LED sources. Luminaire body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame. The product ensures a homogeneous distribution of light on the iris without shadows and lighter points directly below the LED sources. Luminaire recommended for: emergency departments, intensive care units, and treatment rooms.

## Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED SMOOTH
Name	RUBIN CLEAN LED S SMOOTH 7500 SHM EDD 34 830 / 1210X310MM
Index	19.4047.3413.34



## Light and electrical data



Light source	LED
Luminous flux LED [lm]	7337,2
LED power [W]	35,6
Luminaire luminous flux [lm]	5804
Power of luminaire [W]	39,9
Luminaire's light efficiency [lm/W]	145,5
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)

**Mechanical data**



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	1210 x 310 x 78

**A graph of light**



cd/klm — C0 - C180 — C90 - C270 η = 79%