

Product: ARTSHAPE LINE WALL L-320 UP&DOWN 650/650 PLX E 34 840 Index: 19.4049.1121.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on the wall. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

Product information		CategoryArchitectural luminairesFamilyARTSHAPE LINE WALLNameARTSHAPE LINE WALL	S L-320 UP&DOWN 650/650 PLX E 34 840
		Index 19.4049.1121.34	
		EAN 5902107237950	
			$\textcircled{E} \textcircled{P} \textcircled{P}_{40} \H{K}_{40} \H{P}_{1000} \H{P}_{10000}$
Light and electrical data		Light source	LED
-		Luminous flux LED [Im]	1420
		LED power [W]	8
		Luminaire luminous flux [lm]	745
		Power of luminaire [W]	9
		Luminaire's light efficiency [lm/W]	82,8
		Color of the light [K]	4000
		CRI	>80
		SDCM (LED sources)	3
		Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
		Photobiological risk class (IEC/EN 62471)	RG0
		Protection against electric shock	I
		Protection degree	IP40
		Voltage	220240 V, 5060 Hz
		Lifetime of LED sources [h]	100000
		Lx/By	L80/B10
		Operating temperature range [°C]	0 ÷ 30
		Driver	standard on/off (E)
		Power factor $\cos \phi$	>0,95
		Circuit load capacity	40 (B10), 60 (B16), 64 (C10), 102 (C16)



Datasheet

Mechanical data

. A .	B

Assembly	mounted on wall
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,2
Dimensions [mm]	320 x 110 x 85

A graph of light

