

Product: AGAT CLEAN NO FRAME LED 2600 MICRO-PRM SH EDD IP65 34 840 / 600X300

Index: 19.4051.1123.34



### **Description**

Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. Luminary recommended for: operating and treatment rooms, as well as intensive care units.

#### **Product information**

Category	Clean luminaires - recessed
Family	AGAT CLEAN NO FRAME LED
Name	AGAT CLEAN NO FRAME LED 2600 MICRO-PRM SH EDD IP65 34 840 / 600X300
Index	19.4051.1123.34
EAN	5902107433611
















## Light and electrical data

Light source	LED	
Luminous flux LED [lm]	2672	
LED power [W]	12,4	
Luminaire luminous flux [lm]	1959	
Power of luminaire [W]	13,9	
Luminaire's light efficiency [lm/W]	140,9	
Color of the light [K]	4000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP65	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 30	
Driver	DIM DALI (EDD)	
Power factor cos φ	>0,95	
Circuit load capacity	20 (B10), 31 (B16), 33 (C10), 53 (C16)	



Mechanical data	Assembly	mounted in module ceilings, as well as plasterboard ceilings
	Material	steel sheet
B	Color	RAL 9016 (white)
	Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
A	Impact resistant	IK08
	Dimensions [mm]	596 x 296 x 76
	Mounting hole [mm]	580 x 280

# A graph of light



### **Accessories**

Index 6BZBO60980

Name Handle for pane opening

