

Product: AGAT CLEAN NO FRAME LED 6600 SHM E IP65 34 840 / 600X600

Index: 19.4052.2421.34



## **Description**

Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. Luminary recommended for: operating and treatment rooms, as well as intensive care units. \*Selected luminary variants are available with ENEC certificate.

### **Product information**

Category	Clean luminaires - recessed
Family	AGAT CLEAN NO FRAME LED
Name	AGAT CLEAN NO FRAME LED 6600 SHM E IP65 34 840 / 600X600
Index	19.4052.2421.34
EAN	5902023895265

















### Light and electrical data

Links assume	LED
Light source	LED
Luminous flux LED [lm]	7013
LED power [W]	32,7
Luminaire luminous flux [lm]	5547
Power of luminaire [W]	36,6
Luminaire's light efficiency [lm/W]	151,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 100000
	,
Lifetime of LED sources [h]	100000
Lifetime of LED sources [h] Lx/By	100000 L80/B10
Lifetime of LED sources [h]  Lx/By  Operating temperature range [°C]	100000 L80/B10 5 ÷ 30




		1 00+0
IVI (-	nanıraı	I Nala
IVICC	hanical	ı aata

		В			 ţн
^	1				

Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Weight [kg]	6,7
Dimensions [mm]	596 x 596 x 76
Mounting hole [mm]	580 x 580

# A graph of light



#### **Accessories**

Index 6BZBO60980

Name Handle for pane opening

