

Product: AGAT CLEAN NO FRAME LED 11000 SHM EDD IP65 34 830 / 600X600

Index: 19.4052.2613.34



Description

Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. Luminary recommended for: operating and treatment rooms, as well as intensive care units.

Product information

Category	Clean luminaires - recessed
Family	AGAT CLEAN NO FRAME LED
Name	AGAT CLEAN NO FRAME LED 11000 SHM EDD IP65 34 830 / 600X600
Index	19.4052.2613.34
EAN	5902107854874
















Light and electrical data

Light source	LED		
Luminous flux LED [lm]	11104		
LED power [W]	54,5		
Luminaire luminous flux [lm]	8783		
Power of luminaire [W]	61		
Luminaire's light efficiency [lm/W]	144		
Color of the light [K]	3000		
CRI	>80		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°		
Photobiological risk class (IEC/EN 62471)	RG0		
Protection against electric shock	I		
Protection degree	IP65		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	100000		
Lx/By	L80/B10		
Operating temperature range [°C]	5 ÷ 30		
Driver	DIM DALI (EDD)		
Driver	51111 57 (LD5)		
Power factor cos φ	>0,95		




Mec			
$\mathbb{R}/(\mathbb{R} \times \mathbb{R})$	000	\sim	1
W/I C/ - I			
	пап	u	ala



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	596 x 596 x 76
Mounting hole [mm]	580 x 580

A graph of light



Accessories

Index 6BZBO60980

Name Handle for pane opening

