

Product: AGAT CLEAN SLIGHT LED 8800 OPTICS-2L SH IP65 E 34 840 / 600X600

Index: 19.4056.2621.34



Description

Luminaire designed to module suspended ceilings. Light distribution made by using high performance lenses. Luminaire body made from steel sheet, powder coated in white. Luminaire recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

Category	Clean luminaires - recessed
Family	AGAT CLEAN SLIGHT LED
Name	AGAT CLEAN SLIGHT LED 8800 OPTICS-2L SH IP65 E 34 840 / 600X600
Index	19.4056.2621.34
EAN	5902107151447



Light and electrical data

Light source	LED
Luminous flux LED [lm]	9350,9
LED power [W]	43,6
Luminaire luminous flux [lm]	7858
Power of luminaire [W]	48,8
Luminaire's light efficiency [lm/W]	161
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 56,4° / 92,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 25 (B16), 24 (C10), 38 (C16)

Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SH (transparent hardened glass)
Impact resistant	IK08
Dimensions [mm]	595 x 595 x 35

A graph of light

