

Product: DOMINO CLEAN LOW UGR LED 6300 SH RASTER DAISY-BLACK-WIDE EDD IP65 34 930 / 592X592MM

Index: 19.4057.1133.34



Description

LED luminaire dedicated to be mounted on suspended modular ceilings. Equipped with highly efficient LED light sources. The Domino Clean LOW UGR LED uses an anti-glare louvre which reduces glare and directs light precisely. Housing made of steel sheet. Significant diversity of the value of luminous flux. Colour rendering index CRI: 80 or 90. Level of tightness IP65.

Product information

Category	Clean luminaires - recessed
Family	DOMINO CLEAN LOW UGR LED
Name	DOMINO CLEAN LOW UGR LED 6300 SH RASTER DAISY-BLACK-WIDE EDD IP65 34 930 / 592X592MM
Index	19.4057.1133.34
EAN	5902107462772



Light and electrical data

Light source	LED
Luminous flux LED [lm]	5847
LED power [W]	32,2
Luminaire luminous flux [lm]	5028
Power of luminaire [W]	36,1
Luminaire's light efficiency [lm/W]	139,3
Color of the light [K]	3000
CRI	>90
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 71,6° / 75,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)

Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	RASTER (anti-glare louver)
Impact resistant	IK08
Dimensions [mm]	592 x 592 x 50

A graph of light

