

Product: TOPAZ ODG CLEAN AL LED 5200 MICRO-PRM SH EDD IP65 33 840 / 600X600

Index: 19.4058.2523.33



## **Description**

Body of the luminaire made of steel sheet powder coated in white. Special construction of the luminaire allows opening it from the top. Thanks to this, maintenance can be done without littering facilities. Product is equipped in highly efficient LED light source. The luminaire recommended for pharmaceutical, electrical and chemical industry.

## **Product information**

Category	Clean luminaires - recessed
Family	TOPAZ ODG CLEAN AL LED
Name	TOPAZ ODG CLEAN AL LED 5200 MICRO-PRM SH EDD IP65 33 840 / 600X600
Index	19.4058.2523.33
EAN	5902107867485
















## Light and electrical data

Light source	LED	
Luminous flux LED [lm]	5343,4	
LED power [W]	24,8	
Luminaire luminous flux [lm]	3917	
Power of luminaire [W]	27,8	
Luminaire's light efficiency [lm/W]	140,9	
Color of the light [K]	4000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP65	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 30	
Driver	DIM DALI (EDD)	
Power factor cos φ	>0,95	
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)	



$\mathbf{N}\mathbf{A} \wedge \mathbf{A}$	han	$\sim$	data
IVIE	пап	IC AII	uala
11100		- Cui	autu



Assembly	for specialty or concrete ceilings
Material	steel sheet
Color	RAL 9010 (white)
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Dimensions [mm]	657 x 626 x 50-105
Mounting hole [mm]	603 x 603

## A graph of light



