

**Product: TOPAZ ODG CLEAN AL LED 11000 PLX EDD IP65 33 830 / 600X600** 

Index: 19.4058.3313.33



## **Description**

Body of the luminaire made of steel sheet powder coated in white. Special construction of the luminaire allows opening it from the top. Thanks to this, maintenance can be done without littering facilities. Product is equipped in highly efficient LED light source. The luminaire recommended for pharmaceutical, electrical and chemical industry.

## **Product information**

Category	Clean luminaires - recessed
Family	TOPAZ ODG CLEAN AL LED
Name	TOPAZ ODG CLEAN AL LED 11000 PLX EDD IP65 33 830 / 600X600
Index	19.4058.3313.33
EAN	5902107867256















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	11104,2
LED power [W]	54,5
Luminaire luminous flux [lm]	8273
Power of luminaire [W]	61
Luminaire's light efficiency [lm/W]	135,6
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 105° / 104,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
	DUL D 41 1 (EDD)
Driver	DIM DALI (EDD)
Driver Power factor cos φ	>0,95



Mechanical data	Assembly	for specialty or concrete ceilings
	Material	steel sheet
	Color	RAL 9010 (white)
B	Diffuser	PLX (PMMA opal)
	Impact resistant	IK04
	Dimensions [mm]	657 x 626 x 50-105
	Mounting hole [mm]	603 x 603

## A graph of light



