

Product: TOPAZ ODG CLEAN ST LED P SMOOTH 7500 SHM E IP65 34 830 / 650X650MM SUFIT 60MM

Index: 19.4059.4211.34



Description

Body of the luminaire made of steel sheet powder coated in white. Special construction of the luminaire allows opening it from the top. Thanks to this, maintenance can be done without littering facilities. The luminaire can be mounted in a ceiling thickness of 55 mm to 75 mm. The product is adapted to be walked on during maintenance. The luminaire withstands 0.9 kN/m2. Product is equipped in highly efficient LED light source. The luminaire recommended for pharmaceutical, electrical and chemical industry.

Product information

| Category | Clean luminaires - recessed |
|----------|---|
| Family | TOPAZ ODG CLEAN ST LED SMOOTH |
| Name | TOPAZ ODG CLEAN ST LED P SMOOTH 7500 SHM E IP65 34 830 / 650X650MM SUFIT 60MM |
| Index | 19.4059.4211.34 |
| EAN | 5902107491864 |















Light and electrical data

| Liebt course | 1.50 | |
|---|---|--|
| Light source | LED | |
| Luminous flux LED [lm] | 7756 | |
| LED power [W] | 36,4 | |
| Luminaire luminous flux [lm] | 6135 | |
| Power of luminaire [W] | 40,8 | |
| Luminaire's light efficiency [lm/W] | 150,4 | |
| Color of the light [K] | 3000 | |
| CRI | >80 | |
| SDCM (LED sources) | 3 | |
| Beam angle [°] | (C0-C180) / (C90-C270) - 109,6° / 109,6° | |
| Photobiological risk class (IEC/EN 62471) | RG0 | |
| Protection against electric shock | I | |
| Protection degree | IP65 | |
| Voltage | 220240 V, 5060 Hz | |
| Lifetime of LED sources [h] | 100000 | |
| Lx/By | L80/B10 | |
| Operating temperature range [°C] | 5 ÷ 30 | |
| Driver | standard on/off (E) | |
| Power factor cos φ | >0,95 | |
| Circuit load capacity | 8 (B10), 13 (B16), 12 (C10), 20 (C16) | |



| Mechanical data | Assembly | mounted in suspended ceiling |
|-----------------|--------------------|------------------------------|
| | Material | steel sheet |
| | Color | RAL 9016 (white) |
| | Diffuser | SHM (hardened mat glass) |
| ŢH | Impact resistant | IK08 |
| A | Dimensions [mm] | 650 x 650 x 55-75 |
| | Mounting hole [mm] | 616 x 616 |

A graph of light

