

Product: TOPAZ ODG CLEAN ST LED P SMOOTH 7500 MICRO-PRM SH E IP65 34 830 / 650X650MM SUFIT 60MM Index: 19.4059.2211.34



Description

Body of the luminaire made of steel sheet powder coated in white. Special construction of the luminaire allows opening it from the top. Thanks to this, maintenance can be done without littering facilities. The luminaire can be mounted in a ceiling thickness of 55 mm to 75 mm. The product is adapted to be walked on during maintenance. The luminaire withstands 0.9 kN/m2. Product is equipped in highly efficient LED light source. The luminaire recommended for pharmaceutical, electrical and chemical industry.

Product information

Category	Clean luminaires - recessed
Family	TOPAZ ODG CLEAN ST LED SMOOTH
Name	TOPAZ ODG CLEAN ST LED P SMOOTH 7500 MICRO-PRM SH E IP65 34 830 / 650X650MM SUFIT 60MM
Index	19.4059.2211.34
EAN	5902107491826
















Light and electrical data

Light source	LED		
Luminous flux LED [lm]	7756		
LED power [W]	36,4		
Luminaire luminous flux [lm]	5685		
Power of luminaire [W]	40,8		
Luminaire's light efficiency [lm/W]	139,3		
Color of the light [K]	3000		
CRI	>80		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°		
Photobiological risk class (IEC/EN 62471)	RG0		
Protection against electric shock	I		
Protection degree	IP65		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	100000		
Lx/By	L80/B10		
Operating temperature range [°C]	5 ÷ 30		
Driver	standard on/off (E)		
Power factor cos φ	>0,95		
Circuit load capacity	8 (B10), 13 (B16), 12 (C10), 20 (C16)		



Mec			
$\mathbb{R}/(\mathbb{R} \times \mathbb{R})$	000	\sim	1
W/I C/ - I			
	пап	u	ala.



Assembly	mounted in suspended ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Dimensions [mm]	650 x 650 x 55-75
Mounting hole [mm]	616 x 616

A graph of light



