


## Product: RUBIN CLEAN CORNER INOX LED 2200 SHM KR E IP65 20 830 / 675X252MM Index: 19.4061.1111.20




## Description

Hermetic luminary dedicated for clean rooms, and other health service structures. Luminary to be surface mounted or in the walls and ceilings corners. Luminary equipped in highly efficient LED sources. Its optical system is equipped with the diffuser made from mat hardened glass. Luminary cover is made from INOX steal. The screws are flushed with the luminary surface to reduce the number of elements and to facilitate its cleaning. Luminary high hermetic feature is provided by silicon seals placed among the elements. Luminary equipped with the protective mesh made from the INOX steal.

Product information	Category Clean luminaires - surface
	Family RUBIN CLEAN CORNER INOX LED
	Name RUBIN CLEAN CORNER INOX LED 2200 SHM KR E IP65 20 830 / 675X252MM
	Index 19.4061.1111.20
	EAN <b>5901867474964</b>
	$\overbrace{LED} \textcircled{\ } \fbox{\ } \textcircled{\ } \r{\ } $
Light and electrical data	Light source LED
	Luminous flux LED [lm] 2196
	LED power [W] <b>10,9</b>
	Luminaire luminous flux [lm] 1318
	Power of luminaire [W] 12,2
	Luminaire's light efficiency [Im/W] 108
	Color of the light [K] 3000
	CRI >80
	SDCM (LED sources) 3
	Beam angle [°] (C0-C180) / (C90-C270) - 93,2° / 78°
	Photobiological risk class (IEC/EN RG0 62471)
	Protection against electric shock
	Protection degree IP65
	Voltage 220240 V, 5060 Hz
	Lifetime of LED sources [h] <b>100000</b>
	Lx/By <b>L80/B10</b>
	Operating temperature range [°C] 5 ÷ 30
	Driver standard on/off (E)
	Power factor $\cos \varphi$ <b>0,96</b>
	Circuit load capacity 46 (B10), 74 (B16), 72 (C10), 115 (C16)

## Mechanical data



## A graph of light

Assembly	surface mounted on ceiling
Material	INOX steel
Color	INOX
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	675 x 252 x 115

