

Product: RUBIN CLEAN CORNER LED 5200 PC E IP65 34 830 / 1230X230MM

Index: 19.4062.1311.34



## Description

Hermetic luminary dedicated for clean rooms, and other health service structures. Luminary to be surface mounted or in the walls and ceilings corners. LED sources of the high illumination efficacy. The luminary body made from steel sheet powder coated in white. Its optical system is equipped with milk polycarbonate, or mat hardened glass diffuser. Luminary recommended to all spaces with the hazards of its destruction. Accessories: steel mesh powder coated in white. Luminary also available without the steel mesh.

## Product information


Category	Clean luminaires - surface
Family	RUBIN CLEAN CORNER LED
Name	RUBIN CLEAN CORNER LED 5200 PC E IP65 34 830 / 1230X230MM
Index	19.4062.1311.34
EAN	5901867466228



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	5076,2
LED power [W]	24,8
Luminaire luminous flux [lm]	3553
Power of luminaire [W]	27,8
Luminaire's light efficiency [lm/W]	127,8
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 95° / 81,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)

## Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK08
Dimensions [mm]	1230 x 263 x 115

## A graph of light

