

**Product:** RUBIN CLEAN LED 2600 SHM EDD IP65 34 830 / 610X310MM

**Index:** 19.4063.3113.34



## Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminaire recommended for: operating and treatment rooms, as well as intensive care units.

## Product information

|          |  |
|----------|--|
| Category | Clean luminaires - surface                           |
| Family   | RUBIN CLEAN LED                                      |
| Name     | RUBIN CLEAN LED 2600 SHM EDD IP65 34 830 / 610X310MM |
| Index    | 19.4063.3113.34                                      |
| EAN      | 5902107085254  |



## Light and electrical data

|   |  |
|---|--|
| Light source                              | LED                                      |
| Luminous flux LED [lm]                    | 2538                                     |
| LED power [W]                             | 12,4                                     |
| Luminaire luminous flux [lm]              | 2008                                     |
| Power of luminaire [W]                    | 13,9                                     |
| Luminaire's light efficiency [lm/W]       | 144,5                                    |
| Color of the light [K]                    | 3000                                     |
| CRI                                       | >80                                      |
| SDCM (LED sources)                        | 3  |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 109,6° / 109,6° |
| Photobiological risk class (IEC/EN 62471) | RG0                                      |
| Protection against electric shock         | I  |
| Protection degree                         | IP65                                     |
| Voltage                                   | 220..240 V, 50..60 Hz                    |
| Lifetime of LED sources [h]               | 100000                                   |
| Lx/By                                     | L80/B10                                  |
| Operating temperature range [°C]          | 5 ÷ 30                                   |
| Driver                                    | DIM DALI (EDD)                           |
| Power factor cos φ                        | >0,95                                    |
| Circuit load capacity                     | 20 (B10), 31 (B16), 33 (C10), 53 (C16)   |

**Mechanical data**



|                  |                            |
|------------------|----------------------------|
| Assembly         | surface mounted on ceiling |
| Material         | steel sheet                |
| Color            | RAL 9016 (white)           |
| Diffuser         | SHM (hardened mat glass)   |
| Impact resistant | IK08                       |
| Dimensions [mm]  | 610 x 310 x 78             |

**A graph of light**



cd/klm — C0 - C180 — C90 - C270 η = 79%