

Product: RUBIN CLEAN LED 8800 PLX EDD IP65 34 840 / 1210X310MM

Index: 19.4065.2223.34



Description

Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminary recommended for: operating and treatment rooms, as well as intensive care units.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED
Name	RUBIN CLEAN LED 8800 PLX EDD IP65 34 840 / 1210X310MM
Index	19.4065.2223.34
EAN	5902107085971



Light and electrical data

Light source	LED
Luminous flux LED [lm]	9351
LED power [W]	43,6
Luminaire luminous flux [lm]	6966
Power of luminaire [W]	48,8
Luminaire's light efficiency [lm/W]	142,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 105° / 104,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	6,8
Dimensions [mm]	1210 x 310 x 78

A graph of light

