

**Product:** RUBIN CLEAN LED 17600 MICRO-PRM SH E IP65 34 830 / 1220X620MM

**Index:** 19.4066.4411.34



## Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminaire recommended for: operating and treatment rooms, as well as intensive care units.

## Product information

|          |   |
|----------|---|
| Category | Clean luminaires - surface                                    |
| Family   | RUBIN CLEAN LED   |
| Name     | RUBIN CLEAN LED 17600 MICRO-PRM SH E IP65 34 830 / 1220X620MM |
| Index    | 19.4066.4411.34   |



## Light and electrical data

|   |                                       |
|---|---------------------------------------|
| Light source                              | LED                                   |
| Luminous flux LED [lm]                    | 17622                                 |
| LED power [W]                             | 93,6                                  |
| Luminaire luminous flux [lm]              | 12686                                 |
| Power of luminaire [W]                    | 100,5                                 |
| Luminaire's light efficiency [lm/W]       | 126,2                                 |
| Color of the light [K]                    | 3000                                  |
| CRI                                       | >80                                   |
| SDCM (LED sources)                        | 3                                     |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 88° / 91,8°  |
| Photobiological risk class (IEC/EN 62471) | RG0                                   |
| Protection against electric shock         | I                                     |
| Protection degree                         | IP65                                  |
| Voltage                                   | 220..240 V, 50..60 Hz                 |
| Lifetime of LED sources [h]               | 100000 (1) / 147000 (2)               |
| Lx/By                                     | L80/B10 (1) / L70/B50 (2)             |
| Operating temperature range [°C]          | 5 ÷ 30                                |
| Driver                                    | standard on/off (E)                   |
| Power factor cos φ                        | >0,95                                 |
| Circuit load capacity                     | 7 (B10), 12 (B16), 12 (C10), 19 (C16) |

**Mechanical data**



|                  |  |
|------------------|--|
| Assembly         | surface mounted on ceiling                                       |
| Material         | steel sheet  |
| Color            | RAL 9016 (white)   |
| Diffuser         | Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass) |
| Impact resistant | IK08   |
| Dimensions [mm]  | 1220 x 620 x 78  |

**A graph of light**

