

Product: RUBIN CLEAN LED 13200 MICRO-PRM E IP65 34 840 / 1220X620MM

Index: 19.4066.1321.34



Description

Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminary recommended for: operating and treatment rooms, as well as intensive care units.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED
Name	RUBIN CLEAN LED 13200 MICRO-PRM E IP65 34 840 / 1220X620MM
Index	19.4066.1321.34
EAN	5902023889707



Light and electrical data

Light source	LED
Luminous flux LED [lm]	14026
LED power [W]	65,4
Luminaire luminous flux [lm]	10954
Power of luminaire [W]	73,2
Luminaire's light efficiency [lm/W]	149,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	12(B10), 20 (B16), 19 (C10), 31 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1220 x 620 x 78

A graph of light

