

**Product:** RUBIN CLEAN LED 8800/900 PLX E IP65 34 830/GREEN / 620X620MM TWO CIRCUIT

**Index:** 19.4067.4551.34



## Description

Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminary recommended for: operating and treatment rooms, as well as intensive care units.

## Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED
Name	RUBIN CLEAN LED 8800/900 PLX E IP65 34 830/GREEN / 620X620MM TWO CIRCUIT
Index	19.4067.4551.34
EAN	5902107856748



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	8883/886
LED power [W]	43,6/6,4
Luminaire luminous flux [lm]	6618/660
Power of luminaire [W]	48,8/8
Luminaire's light efficiency [lm/W]	135,6/82,5
Color of the light [K]	3000/green colour
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 105° / 104,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	7 (B10), 12 (B16), 12 (C10), 19 (C16)

**Mechanical data**



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	620 x 620 x 78

**A graph of light**

