

Product: RUBIN CLEAN LED 5200/7000 SHM EDD IP65 34 830/YELLOW MONO / 620X620MM TWO CIRCUIT

Index: 19.4067.1381.34



Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminaire recommended for: operating and treatment rooms, as well as intensive care units.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED
Name	RUBIN CLEAN LED 5200/7000 SHM EDD IP65 34 830/YELLOW MONO / 620X620MM TWO CIRCUIT
Index	19.4067.1381.34
EAN	5902107856526



Light and electrical data

Light source	LED
Luminous flux LED [lm]	5076/6942
LED power [W]	24,8/97,2
Luminaire luminous flux [lm]	4015/5491
Power of luminaire [W]	27,8/108,9
Luminaire's light efficiency [lm/W]	144,4/50,4
Color of the light [K]	3000/yellow colour (dominant wavelength $\lambda_p=592$ nm)
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos ϕ	>0,95
Circuit load capacity	7 (B10), 11 (B16), 7 (C10), 11 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	620 x 620 x 78

A graph of light

