

Product: RUBIN CLEAN LED 5200/800 MICRO-PRM EDD IP65 34 840/RED / 620X620MM TWO CIRCUIT

Index: 19.4067.1543.34



Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminaire recommended for: operating and treatment rooms, as well as intensive care units.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED
Name	RUBIN CLEAN LED 5200/800 MICRO-PRM EDD IP65 34 840/RED / 620X620MM TWO CIRCUIT
Index	19.4067.1543.34
EAN	5902107856717



Light and electrical data

Light source	LED
Luminous flux LED [lm]	5343/857
LED power [W]	24,8/8,8
Luminaire luminous flux [lm]	4173/669
Power of luminaire [W]	27,8/11
Luminaire's light efficiency [lm/W]	150,1/60,8
Color of the light [K]	4000/red colour
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	8 (B10), 14 (B16), 13 (C10), 20 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	620 x 620 x 78

A graph of light

