

Product: RUBIN CLEAN LED 5200/900 PLX E IP65 34 840/GREEN / 620X620MM TWO CIRCUIT

Index: 19.4067.2553.34



Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminary recommended for: operating and treatment rooms, as well as intensive care units.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN LED
Name	RUBIN CLEAN LED 5200/900 PLX E IP65 34 840/GREEN / 620X620MM TWO CIRCUIT
Index	19.4067.2553.34
EAN	5902107488475



Light and electrical data

Light source	LED
Luminous flux LED [lm]	5343/886
LED power [W]	24,8/6,4
Luminaire luminous flux [lm]	3981/660
Power of luminaire [W]	27,8/8
Luminaire's light efficiency [lm/W]	143,2/82,5
Color of the light [K]	4000/green colour
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 105° / 104,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	12 (B10), 20 (B16), 19 (C10), 31 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	620 x 620 x 78

A graph of light

