

**Product:** RUBIN CLEAN LED 5200/7000 SHM E IP65 34 840/YELLOW MONO / 620X620MM TWO CIRCUIT

**Index:** 19.4067.3121.34



## Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminaire recommended for: operating and treatment rooms, as well as intensive care units.

## Product information


|          |   |
|----------|---|
| Category | Clean luminaires - surface  |
| Family   | RUBIN CLEAN LED   |
| Name     | RUBIN CLEAN LED 5200/7000 SHM E IP65 34 840/YELLOW MONO / 620X620MM TWO CIRCUIT |
| Index    | 19.4067.3121.34   |



## Light and electrical data

|   |   |
|---|---|
| Light source                              | LED   |
| Luminous flux LED [lm]                    | 5234/7000   |
| LED power [W]                             | 27+176  |
| Luminaire luminous flux [lm]              | 4213/5634   |
| Power of luminaire [W]                    | 28+198  |
| Luminaire's light efficiency [lm/W]       | 150/28  |
| Color of the light [K]                    | 4000/yellow colour (dominant wavelength $\lambda_p=592$ nm) |
| CRI                                       | >80   |
| SDCM (LED sources)                        | 3   |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 109,6° / 109,6°                    |
| Photobiological risk class (IEC/EN 62471) | RG0   |
| Protection against electric shock         | I   |
| Protection degree                         | IP65  |
| Voltage                                   | 220..240 V, 50..60 Hz                                       |
| Lifetime of LED sources [h]               | 60000   |
| Lx/By                                     | L70/B50   |
| Operating temperature range [°C]          | 5 ÷ 30  |
| Driver                                    | standard on/off (E)   |
| Circuit load capacity                     | 2 (B10), 4 (B16), 4 (C10), 6 (C16)                          |

## Mechanical data



|                  |                            |
|------------------|----------------------------|
| Assembly         | surface mounted on ceiling |
| Material         | steel sheet                |
| Color            | RAL 9016 (white)           |
| Diffuser         | SHM (hardened mat glass)   |
| Impact resistant | IK08                       |
| Weight [kg]      | 9,4                        |
| Dimensions [mm]  | 620 x 620 x 78             |

## A graph of light

