


Product: RUBIN CLEAN NO FRAME LED 5200 SHM EDD IP65 34 840 / 574X574MM

Index: 19.4069.2223.34



Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. Luminary recommended for: operating and treatment rooms, as well as intensive care units.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN NO FRAME LED
Name	RUBIN CLEAN NO FRAME LED 5200 SHM EDD IP65 34 840 / 574X574MM
Index	19.4069.2223.34
EAN	5902107084141



Light and electrical data

Light source	LED
Luminous flux LED [lm]	5343
LED power [W]	24,8
Luminaire luminous flux [lm]	4226
Power of luminaire [W]	27,8
Luminaire's light efficiency [lm/W]	152
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

Mechanical data

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	574 x 574 x 69

A graph of light

Accessories

Index 6BZBO60980

Name Handle for pane opening

