


Product: RUBIN CLEAN NO FRAME LED 8800 SHM EDD IP65 34 830 / 1174X274MM

Index: 19.4070.2213.34



### **Description**

Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. Luminary recommended for: operating and treatment rooms, as well as intensive care units.

#### **Product information**

Category	Clean luminaires - surface
Family	RUBIN CLEAN NO FRAME LED
Name	RUBIN CLEAN NO FRAME LED 8800 SHM EDD IP65 34 830 / 1174X274MM
Index	19.4070.2213.34
EAN	5902107489854
















## Light and electrical data

Light source	LED	
Luminous flux LED [lm]	8883	
LED power [W]	43,6	
Luminaire luminous flux [lm]	7026	
Power of luminaire [W]	48,8	
Luminaire's light efficiency [lm/W]	144	
Color of the light [K]	3000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	1	
i rotection against electric shock		
Protection degree	IP65	
	IP65 220240 V, 5060 Hz	
Protection degree		
Protection degree Voltage	220240 V, 5060 Hz	
Protection degree  Voltage  Lifetime of LED sources [h]	220240 V, 5060 Hz 100000	
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By	220240 V, 5060 Hz 100000 L80/B10	
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By  Operating temperature range [°C]	220240 V, 5060 Hz 100000 L80/B10 5 ÷ 30	



Mechanical data			Assembly	surface mounted on ceiling
	<del></del>	В	Material	steel sheet
			Color	RAL 9016 (white)
	В		Diffuser	SHM (hardened mat glass)
		‡H	Impact resistant	IK08
_ A			Dimensions [mm]	1174 x 274 x 69

# A graph of light



#### **Accessories**

Index 6BZBO60980

Name Handle for pane opening

