

Product: AGAT CLEAN-ECO LED CRI95 7200 SHM E IP65 34 940 / 1200X300

Index: 19.4072.6241.34



## **Description**

LUXIONA Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Luminary designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

## **Product information**

Category	Clean luminaires CRI95
Family	AGAT CLEAN-ECO LED CRI95
Name	AGAT CLEAN-ECO LED CRI95 7200 SHM E IP65 34 940 / 1200X300
Index	19.4072.6241.34
EAN	5902107262853















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	8284
LED power [W]	48,4
Luminaire luminous flux [lm]	6884
Power of luminaire [W]	54,2
Luminaire's light efficiency [lm/W]	127
Color of the light [K]	4000
CRI	>95
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)



Mechanical data	Assembly	mounted in module ceilings
	Material	steel sheet
	Color	RAL 9016 (white)
	Diffuser	SHM (hardened mat glass)
ŢH	Impact resistant	IK08
A	Dimensions [mm]	1196 x 296 x 75



