

**Product:** AGAT CLEAN-ECO LED CRI95 5400 SHM E IP65 34 940 / 600X600

**Index:** 19.4072.3141.34



## Description

LUXIONA Poland as the only company in Europe has obtained CRI>95 for its luminaires (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminaire recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering „deep red” color, and R13 responsible for rendering „light orange” color). Luminaire designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminaire recommended for: emergency departments, intensive care units, and treatment rooms.

## Product information

|          |   |
|----------|---|
| Category | Clean luminaires CRI95                                    |
| Family   | AGAT CLEAN-ECO LED CRI95                                  |
| Name     | AGAT CLEAN-ECO LED CRI95 5400 SHM E IP65 34 940 / 600X600 |
| Index    | 19.4072.3141.34   |
| EAN      | 5902107262488   |



## Light and electrical data


|   |  |
|---|--|
| Light source                              | LED                                      |
| Luminous flux LED [lm]                    | 6213                                     |
| LED power [W]                             | 36,3                                     |
| Luminaire luminous flux [lm]              | 5163                                     |
| Power of luminaire [W]                    | 40,7                                     |
| Luminaire's light efficiency [lm/W]       | 126,9                                    |
| Color of the light [K]                    | 4000                                     |
| CRI                                       | >95                                      |
| SDCM (LED sources)                        | 3  |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 109,6° / 109,6° |
| Photobiological risk class (IEC/EN 62471) | RG0                                      |
| Protection against electric shock         | I  |
| Protection degree                         | IP65                                     |
| Voltage                                   | 220..240 V, 50..60 Hz                    |
| Lifetime of LED sources [h]               | 100000                                   |
| Lx/By                                     | L80/B10                                  |
| Operating temperature range [°C]          | 5 ÷ 30                                   |
| Driver                                    | standard on/off (E)                      |
| Power factor cos φ                        | >0,95                                    |
| Circuit load capacity                     | 25 (B10), 40 (B16), 39 (C10), 62 (C16)   |

**Mechanical data**



|                  |                                   |
|------------------|-----------------------------------|
| Assembly         | <b>mounted in module ceilings</b> |
| Material         | <b>steel sheet</b>                |
| Color            | <b>RAL 9016 (white)</b>           |
| Diffuser         | <b>SHM (hardened mat glass)</b>   |
| Impact resistant | <b>IK08</b>                       |
| Weight [kg]      | <b>6,5</b>                        |
| Dimensions [mm]  | <b>596 x 596 x 75</b>             |

**A graph of light**



**Accessories**

Index 2C1A7392  
 Name Adaptive frame for plasterboard ceiling (600x600)

