

Product: AGAT CLEAN-ECO LED CRI95 7200 SHM E IP65 34 940 / 600X600

Index: 19.4072.3241.34



### **Description**

LUXIONA Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Luminary designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

#### **Product information**

Category Clean luminaires CRI95
Family AGAT CLEAN-ECO LED CRI95
Name AGAT CLEAN-ECO LED CRI95 7200 SHM E IP65 34 940 / 600X600
Index 19.4072.3241.34
















### Light and electrical data

| Light source                              | LED                                       |
|---|---|
| Luminous flux LED [lm]                    | 8284                                      |
| LED power [W]                             | 48,4                                      |
| Luminaire luminous flux [lm]              | 6884                                      |
| Power of luminaire [W]                    | 54,2                                      |
| Luminaire's light efficiency [lm/W]       | 127                                       |
| Color of the light [K]                    | 4000                                      |
| CRI                                       | >95                                       |
| SDCM (LED sources)                        | 3   |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 100° /<br>100,2° |
| Photobiological risk class (IEC/EN 62471) | RG0                                       |
| Protection against electric shock         | I   |
| Protection degree                         | IP65                                      |
| Voltage                                   | 220240 V, 5060 Hz                         |
| Lifetime of LED sources [h]               | 100000                                    |
| Lx/By                                     | L80/B10                                   |
| Operating temperature range [°C]          | 5 ÷ 30                                    |
| Driver                                    | standard on/off (E)                       |
| Power factor cos φ                        | >0,95                                     |
| Circuit load capacity                     | 16 (B10), 26 (B16), 23 (C10), 37 (C16)    |




## Mechanical data



| Assembly         | mounted in module ceilings |
|------------------|----------------------------|
| Material         | steel sheet                |
| Color            | <b>RAL 9016 (white)</b>    |
| Diffuser         | SHM (hardened mat glass)   |
| Impact resistant | IK08                       |
| Weight [kg]      | 6,5                        |
| Dimensions [mm]  | 596 x 596 x75              |

# A graph of light





### **Accessories**

Index 2C1A7392-34R

Name EUROPANEL / BACKPANEL / RIM COMPACT LED RECESSED ACCESSORIES 34 / 600X600

