

Product: AGAT CLEAN LED CRI95 5400 MICRO-PRM EDD IP65 34 940 / 600X600

Index: 19.4073.1243.34



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Luminary designed to module and gypsum and cardboard suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame.

Product information

Category	Clean luminaires CRI95
Family	AGAT CLEAN LED CRI95
Name	AGAT CLEAN LED CRI95 5400 MICRO-PRM EDD IP65 34 940 / 600X600
Index	19.4073.1243.34
EAN	5902107082659















Light and electrical data

Light source	LED				
Luminous flux LED [lm]	6213				
LED power [W]	36,3				
Luminaire luminous flux [lm]	4852				
Power of luminaire [W]	40,7				
Luminaire's light efficiency [lm/W]	119,2				
Color of the light [K]	4000				
CRI	>95				
SDCM (LED sources)	3				
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°				
Photobiological risk class (IEC/EN 62471)	RG0				
Protection against electric shock	I				
Protection degree	IP65				
Voltage	220240 V, 5060 Hz				
Lifetime of LED sources [h]	100000				
Lx/By	L80/B10				
Operating temperature range [°C]	5 ÷ 30				
Driver	DIM DALI (EDD)				
Power factor cos φ	>0,95				
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)				




hanical	

	В			‡н

Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	5,75
Dimensions [mm]	596 x 596 x 76
Mounting hole [mm]	580 x 580

A graph of light



Accessories

Index 2M-X414LKPIPT5

Name Mounting clips set for plasterboard

