

Product: AGAT CLEAN LED CRI95 5400 SHM E IP65 34 940 / 600X600

Index: 19.4073.3241.34



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Luminary designed to module and gypsum and cardboard suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame.

Product information

Category	Clean luminaires CRI95
Family	AGAT CLEAN LED CRI95
Name	AGAT CLEAN LED CRI95 5400 SHM E IP65 34 940 / 600X600
Index	19.4073.3241.34
EAN	5901867494153
















Light and electrical data

Light course	LED
Light source	
Luminous flux LED [lm]	6213
LED power [W]	36,3
Luminaire luminous flux [lm]	4914
Power of luminaire [W]	40,7
Luminaire's light efficiency [lm/W]	120,7
Color of the light [K]	4000
CRI	>95
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Drotootion dograe	
Protection degree	IP65
Voltage	IP65 220240 V, 5060 Hz
Voltage	220240 V, 5060 Hz
Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 100000
Voltage Lifetime of LED sources [h] Lx/By	220240 V, 5060 Hz 100000 L80/B10
Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	220240 V, 5060 Hz 100000 L80/B10 5 ÷ 30




Mec	221	0010	12+2
		Cal (ıaıa
11100	100111	Ou: C	- CLU



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Weight [kg]	7,7
Dimensions [mm]	596 x 596 x 76
Mounting hole [mm]	580 x 580

A graph of light



Accessories

Index 2M-X414LKPIPT5

Name Mounting clips set for plasterboard

