

Product: AGAT CLEAN LED CRI95 14400 SHM E IP65 34 940 / 1200X600

Index: 19.4073.3741.34



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Luminary designed to module and gypsum and cardboard suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame.

Product information

Category	Clean luminaires CRI95
Family	AGAT CLEAN LED CRI95
Name	AGAT CLEAN LED CRI95 14400 SHM E IP65 34 940 / 1200X600
Index	19.4073.3741.34
EAN	5901867494078
















Light and electrical data

Light source	LED	
Luminous flux LED [lm]	16568	
LED power [W]	96,8	
Luminaire luminous flux [lm]	13105	
Power of luminaire [W]	108,4	
Luminaire's light efficiency [lm/W]	120,9	
Color of the light [K]	4000	
CRI	>95	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP65	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 30	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	
Circuit load capacity	8 (B10), 13 (B16), 11 (C10), 18 (C16)	



Mechanical data	Assembly	mounted in module ceilings, as well as plasterboard ceilings
	Material	steel sheet
B	Color	RAL 9016 (white)
	Diffuser	SHM (hardened mat glass)
Α	Impact resistant	IK08
 	Weight [kg]	13,7
	Dimensions [mm]	1196 x 596 x 76
	Mounting hole [mm]	1180 x 580

A graph of light



Accessories

Index 2M-X414LKPIPT5

Name Mounting clips set for plasterboard

