

Product: AGAT CLEAN NO FRAME LED CRI95 3600 MICRO-PRM SH E IP65 34 940 / 600X300

Index: 19.4074.1141.34



### **Description**

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Luminary designed to module and gypsum and cardboard suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

#### **Product information**

Category	Clean luminaires CRI95
Family	AGAT CLEAN NO FRAME LED CRI95
Name	AGAT CLEAN NO FRAME LED CRI95 3600 MICRO-PRM SH E IP65 34 940 / 600X300
Index	19.4074.1141.34
EAN	5901867494528
















#### Light and electrical data

Light source	LED
Luminous flux LED [lm]	4142
LED power [W]	24,2
Luminaire luminous flux [lm]	3036
Power of luminaire [W]	27,1
Luminaire's light efficiency [lm/W]	112
Color of the light [K]	4000
CRI	>95
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data	Assembly	mounted in module ceilings, as well as plasterboard ceilings
	Material	steel sheet
В	Color	RAL 9016 (white)
	Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
A ,	Impact resistant	IK08
	Dimensions [mm]	596 x 296 x 76
	Mounting hole [mm]	580 x 280

# A graph of light



## **Accessories**

Index 6BZBO60980

Name Handle for pane opening

