

Product: AGAT CLEAN NO FRAME LED CRI95 5400 SHM EDD IP65 34 940 / 600X600

Index: 19.4074.2243.34



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Luminary designed to module and gypsum and cardboard suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

Product information

| Category | Clean luminaires CRI95 |
|----------|--|
| Family | AGAT CLEAN NO FRAME LED CRI95 |
| Name | AGAT CLEAN NO FRAME LED CRI95 5400 SHM EDD IP65 34 940 / 600X600 |
| Index | 19.4074.2243.34 |
| EAN | 5902107082925 |
















Light and electrical data

| Light source | LED | |
|--|--|--|
| Luminous flux LED [lm] | 6213 | |
| LED power [W] | 36,3 | |
| Luminaire luminous flux [lm] | 4914 | |
| Power of luminaire [W] | 40,7 | |
| Luminaire's light efficiency [lm/W] | 120,7 | |
| Color of the light [K] | 4000 | |
| CRI | >95 | |
| SDCM (LED sources) | 3 | |
| Beam angle [°] | (C0-C180) / (C90-C270) - 109,6° / 109,6° | |
| Photobiological risk class (IEC/EN 62471) | RG0 | |
| Protection against electric shock | I | |
| | | |
| Protection degree | IP65 | |
| Protection degree Voltage | IP65 220240 V, 5060 Hz | |
| | | |
| Voltage | 220240 V, 5060 Hz | |
| Voltage Lifetime of LED sources [h] | 220240 V, 5060 Hz 100000 | |
| Voltage Lifetime of LED sources [h] Lx/By | 220240 V, 5060 Hz 100000 L80/B10 | |
| Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] | 220240 V, 5060 Hz 100000 L80/B10 5 ÷ 30 | |




| $\mathbf{n} / \mathbf{n} \sim \mathbf{n}$ | Shop | 100 | 20+0 |
|---|-------------|------|-------|
| W C | | | 11212 |
| IVIC | , nan | ıvaı | data |



| Assembly | mounted in module ceilings, as well as plasterboard ceilings |
|--------------------|--|
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | SHM (hardened mat glass) |
| Impact resistant | IK08 |
| Dimensions [mm] | 596 x 596 x 76 |
| Mounting hole [mm] | 580 x 580 |

A graph of light



Accessories

Index 6BZBO60980

Name Handle for pane opening

