

Product: AGAT CLEAN NO FRAME LED CRI95 7200 SHM EDD IP65 34 930 / 600X600

Index: 19.4074.2333.34



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Luminary designed to module and gypsum and cardboard suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

Product information

Category	Clean luminaires CRI95
Family	AGAT CLEAN NO FRAME LED CRI95
Name	AGAT CLEAN NO FRAME LED CRI95 7200 SHM EDD IP65 34 930 / 600X600
Index	19.4074.2333.34
EAN	5902107866242
















Light and electrical data

Light source	LED	
Luminous flux LED [lm]	7952,6	
LED power [W]	48,4	
Luminaire luminous flux [lm]	6291	
Power of luminaire [W]	54,2	
Luminaire's light efficiency [lm/W]	116,1	
Color of the light [K]	3000	
CRI	>95	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP65	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 30	
Driver	DIM DALI (EDD)	
Power factor cos φ	>0,95	
. σ.	-0,55	




$\mathbf{n} / \mathbf{n} \sim \mathbf{n}$	Shop	100	20+0
W C			11212
IVIC	, nan	ıvaı	data



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	596 x 596 x 76
Mounting hole [mm]	580 x 580

A graph of light



Accessories

Index 6BZBO60980

Name Handle for pane opening

