

Product: RUBIN CLEAN LED CRI95 7200 PLX EDD IP65 34 940 / 1210X310MM

Index: 19.4075.2443.34



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame.

Product information

Category	Clean luminaires CRI95
Family	RUBIN CLEAN LED CRI95
Name	RUBIN CLEAN LED CRI95 7200 PLX EDD IP65 34 940 / 1210X310MM
Index	19.4075.2443.34
EAN	5902107065034















Light and electrical data

Light source	LED
Luminous flux LED [lm]	8284
LED power [W]	48,4
Luminaire luminous flux [lm]	6172
Power of luminaire [W]	54,2
Luminaire's light efficiency [lm/W]	113,9
Color of the light [K]	4000
CRI	>95
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 105° / 104,8°
Photobiological risk class (IEC/EN 62471)	RG0
02-11-1)	
Protection against electric shock	I
,	I IP65
Protection against electric shock	•
Protection against electric shock Protection degree	IP65
Protection against electric shock Protection degree Voltage	IP65 220240 V, 5060 Hz
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h]	IP65 220240 V, 5060 Hz 100000
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By	IP65 220240 V, 5060 Hz 100000 L80/B10
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	IP65 220240 V, 5060 Hz 100000 L80/B10 5 ÷ 30



Mechanical data	Assembly	surface mounted on ceiling
	Material	steel sheet
	Color	RAL 9016 (white)
l B	Diffuser	PLX (PMMA opal)
ŢH	Impact resistant	IK04
A	Weight [kg]	6,09
	Dimensions [mm]	1210 x 310 x 78

A graph of light

