

**Product:** RUBIN CLEAN NO FRAME LED CRI95 3600 MICRO-PRM SH EDD IP65 34 930 / 574X274MM

**Index:** 19.4076.1133.34



## Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaires (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminaire recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering „deep red” color, and R13 responsible for rendering „light orange” color). Surface mounted luminaire equipped in highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminaire body.

## Product information

Category	Clean luminaires CRI95
Family	RUBIN CLEAN NO FRAME LED CRI95
Name	RUBIN CLEAN NO FRAME LED CRI95 3600 MICRO-PRM SH EDD IP65 34 930 / 574X274MM
Index	19.4076.1133.34
EAN	5902107867010



## Light and electrical data


Light source	LED
Luminous flux LED [lm]	3976
LED power [W]	24,2
Luminaire luminous flux [lm]	2914
Power of luminaire [W]	27,1
Luminaire's light efficiency [lm/W]	107,5
Color of the light [K]	3000
CRI	>95
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

**Mechanical data**



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Dimensions [mm]	574 x 274 x 69

**A graph of light**



**Accessories**

Index 6BZBO60980  
Name Handle for pane opening

